



Caribbean
Paint
Factory
Aruba Inc.

EURO FIX SPECIAL

Interior/Exterior Water-Based Clear Masonry Primer Sealer

8205

DESCRIPTION

Our traditional clear sealer based on an acrylic copolymer specifically designed to seal and condition masonry surfaces. May be used on interior and exterior concrete, stucco, precast concrete, plaster and previously painted surfaces that are worn and chalky. May be used under alkyd, latex, acrylic, or elastomeric smooth and textured finishes. Features excellent penetration and adhesion over chalky surfaces.

FEATURES

- ▶ Adhesion over chalky surfaces
- ▶ Excellent penetration
- ▶ Seals and strengthens masonry surfaces
- ▶ Promotes adhesion
- ▶ Alkali resistant

COMPOSITION

- ▶ Modified Acrylic Resin
- ▶ Not manufactured with lead or mercury containing materials

SPECIFICATION DATA

Color:
Clear

Finish:
Semi-gloss

Clean up solvent:
Mineral Spirits

Density:
1.5 g/cm³

VOC:
1,42 lbs/gal (170 g/L)

Solids:
Volume: 36 +/- 2%

Practical coverage:
Apply at 350-450 sq ft/gal (9-11 m²/L)

Actual coverage depending on type and structure of substrate and application method

Dry Time:
77°F (25°C) & 50% RH:

To touch – 1 hour
To recoat – 4 hours



FINISHES | PAINTING (08900)

⚠ Read Label and Material Safety Data Sheet Prior to Use.
See other cautions on last page.

www.cpfaruba.com

Caribbean Paint Factory Aruba Inc.

Tel: +297 - 5825339

Fax: +297 - 5837063

Sabana Blanco 16A
Oranjestad - Aruba

SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

NEW SURFACES

Concrete, Plaster and Masonry - Cure for 30 days before painting. Poured concrete or pre-cast concrete needs chemical cleaning or a light sand blasting. Rinse completely with water and allow to fully dry. Remove loose aggregate and prime with this product. For concrete block, fill and level with a Euro Block Filler.

PREVIOUSLY PAINTED SURFACES

Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose or peeling paint to sound surface by high pressure water cleaning. Remove all mildew by washing with a solution of 16 oz (473 mL) liquid household bleach and two oz (59 mL) non-ammoniated liquid detergent per gallon (3.785 L) of water. Rinse surface clean with water and allow to dry. Prime with this product.

DIRECTIONS FOR USE

Tools - Use a 1/2" or larger nap roller [lamb's wool rollers recommended for the professional] and a quality brush. No thinning required.

Painting & Cleaning – Do not paint if rain, snow, heavy dew or lower temperatures are expected within two hours of painting. Clean hands and tools with white spirit.

SHIPPING

Freight Classification:

Paint, Freezable

Packaging:

1 gallon (3.785L)

Flash Point:

44°C (111°F)

! LIMITATIONS OF LIABILITY

The information in this data sheet is based on laboratory tests we believe to be accurate and is intended for guidance purposes only. All recommendations or suggestions relating to the use of the products made by Caribbean Paint Factory Aruba, whether in technical documentation, or in response to a specific inquiry, or otherwise, are based on data which to the best of our knowledge are reliable. The products and information are designed for users having the requisite knowledge and industrial skills and it is the end user's responsibility to determine the suitability of the product for its intended use. Caribbean Paint Factory Aruba has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Caribbean Paint Factory does therefore not accept liability arising from loss, injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise) The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is therefore the user's responsibility to ensure that this sheet is current prior to using the product. The English text of this document shall prevail over any translation thereof.

8205 – November 2009

www.cpfaruba.com

Caribbean Paint Factory Aruba Inc.
Tel: +297 - 5825339
Fax: +297 - 5837063
Sabana Blanco 16A
Oranjestad - Aruba

