



GLIDDEN™ SPRED®
Exterior Latex Satin Paint
SP29XX

DESCRIPTION

GLIDDEN SPRED exterior satin paint is ideal for all exterior siding, eaves and downspouts. **GLIDDEN** exterior is specially formulated with 100% acrylic latex to protect against UV rays, color fading and severe weather conditions. Additionally, all **GLIDDEN SPRED** exterior paints provide a mildew resistant coating and can be applied in low temperatures (above 35°F) which allow you to extend the painting season with confidence.

FEATURES

- Resists Dirt
- Fade Resistant
- Provides a Mildew Resistant Coating

COMPOSITION

- 100% Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION DATA

Color:

White, ready mix & custom colors

Finish:

Satin, 25-38 units @85°

Clean-up Solvent:

Soap & water

Density:

10.14 lbs/gal (1.22 kg/L)

VOC:

0.38 lbs/gal (46 g/L)

Solids:

Volume - 36% +/- 1%

Weight - 45% +/- 1%

Practical Coverage:

Apply at 300-400 sq ft/gal (7-10 m²/L).
Actual coverage may vary depending on substrate and application method.

Flash Point:

None

Dry Time

77°F (25°C) & 50% RH:

To touch – 1 hour

To recoat - 4 Hours

35°F (2°C)

To touch – 3-6 hours

To recoat – 24 hours

SURFACE PREPARATION

Fill all holes, cracks or open joints with caulk • Lightly sand glossy areas.

Make sure all areas are clean, sound and free of flaking paint or any substances such as oil, grease, dirt...anything that will get between your siding and your paint. Prepare *Previously Painted Surfaces* with this product or **GLIDDEN** Prime Exteriors PC3000 acrylic primer/sealer.

IT IS TIME TO PRIME - PREPARING UNPAINTED SURFACES

WOOD - Sand lightly to a smooth surface, then prime woods prone to cracking such as yellow pine or T-1-11 plywood siding with this product or **GLIDDEN** Prime Exteriors PC3000 acrylic primer/sealer. Prime tannin containing woods such as redwood or cedar with **GLIDDEN** Prime Exteriors PC3000 acrylic primer/sealer.

CONCRETE, PLASTER AND MASONRY - Cure for 30 days before painting. "Slick poured" or pre-cast concrete needs chemical

cleaning or a light sandblasting. Thoroughly rinse with water and allow to fully dry. Remove loose aggregate and prime with a **GLIDDEN** primer. For concrete block, fill with a **GLIDDEN** block filler.

STEEL, GALVANIZED METAL AND ALUMINUM - Clean off oils, then prime with a **GLIDDEN** primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

QUALITY TOOLS FOR A QUALITY JOB

Use a 1/2" or larger nap roller and a nylon or polyester brush/paint pad for siding • For trim use 1/2" or small nap roller • May also be applied using airless spray with a .015" to .017" tip at 2000 to 2500 psi pressure.

LET'S GET PAINTING

Mix thoroughly • Apply at package consistency • Thin with 1/2 pint water per gallon if necessary only when using a sprayer • Make sure the air, paint and the surface you are painting are above 35° F • Do not paint if rain, snow, heavy dew or lower temperatures are expected within two hours of painting • Apply generously, no

overspreading • Certain colors may require more than one coat for complete hide.

1. Stir with a lifting motion for uniform color.
2. Dampen roller slightly with water.
3. Paint all trim including, windows, shutters & door frames first.
4. Begin at highest point, working towards the ground.

LET'S CLEAN UP

Clean hands and tools with warm, soapy water • Clean spills right away with a damp cloth • After 30 days or paint has fully cured, areas may be washed with a non-abrasive, mild detergent.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe the vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS4-1105

SHIPPING

FREIGHT CLASSIFICATION:
Paint. Freezable

PACKAGING:
4 quart (0.946 L)
1 gallon (3.785 L)
5 gallon (18.925 L)

FLASH POINT:
None

www.cpfaruba.com

Technical and Trademark License Holders

Caribbean Paint Factory Aruba Inc.
Tel: +297 - 5825339
Fax: +297 - 5837063
Sabana Blanco 16A
Oranjestad - Aruba

