



Caribbean
Paint
Factory
Aruba Inc.

EURO MARINE®

Interior/Exterior High Gloss Modified Alkyd Enamel
8050-X

DESCRIPTION

A premium quality modified alkyd gloss enamel for use on machinery, equipment, piping, doors tank exteriors and commercial steel structures. Particularly suitable as a finish for boat top, top side, deck and deck equipment. Toughness and fast dry provides maintenance with minimum interruption.

FEATURES

- ▶ Protects against atmospheric corrosion
- ▶ Excellent flow and leveling
- ▶ Good abrasion resistance
- ▶ Easy application
- ▶ Excellent resistance to oil, grease and water
- ▶ Good color and gloss retention

COMPOSITION

- ▶ Alkyd Resin
- ▶ Titanium Dioxide and Extender Pigments

SPECIFICATION DATA

Color:
White & Custom Colors

Finish:
High Gloss

Clean up solvent:
Mineral Spirits

Density:
9.58 lbs/gal (1.15 kg/L)

VOC:
1.15 lbs/gal (138 g/L)

Solids:
Volume: 53 +/- 2%

Practical coverage:
Apply at 350-450 sq ft/gal (9-11 m²/L)
Actual coverage depending on type and structure of substrate and application method

Dry Time:
77°F (25°C) & 50% RH:
To touch – 1 hour
To recoat – Overnight



FINISHES
PAINTING (08900)

! Read Label and Material Safety Data Sheet Prior to Use.
See other cautions on last page.

www.cpfaruba.com

Caribbean Paint Factory Aruba Inc.
Tel: +297 - 5825339
Fax: +297 - 5837063
Sabana Blanco 16A
Oranjestad - Aruba

SURFACE REPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, rust scale, loose and flaking paint and other foreign substances.

NEWSURFACES

Wood - Prime with Camarol or this product, use wood combination fillers to level surface imperfections. Sand accordingly. Apply finish using this product or Euro Color / Euro Tex or Euro Acryl.

Steel – best results are obtained over a surface sandblasted to a Commercial Blast (SSPC-SP6). Performance over hand or power tool cleaned surfaces is dependent on the degree of cleaning. Prime with suitable primer

Metal&aluminum – Prime galvanized metal or aluminum with a galvanized metal primer.

Concrete, Plaster and Masonry – Cure at least 30 days before painting. Ph must be 10.0 or lower. Poured concrete or pre-cast concrete needs chemical cleaning or a light sand blasting. Rinse completely with water and allow to fully dry. Remove loose aggregate and prime with this product or Euro Fix Special primer/sealer. For concrete block, fill and level with a Euro Block Filler.

PREVIOUSLY PAINTED SURFACES

Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose or peeling paint to sound surface by high pressure water cleaning. Remove all mildew by washing with a solution of 16 oz (473 mL) liquid household bleach and two oz (59 mL) non-ammoniated liquid detergent per gallon (3.785 L) of water. Rinse surface clean with water and allow to dry. Prime with this product.

DIRECTIONS FOR USE

Tools – May be applied by brush, roller or spray. For airless spray use a 0.13" tip. Adjust pressure as needed. Do not apply in damp weather or when surface or air temperature is below 4°C (40°F)

Painting & Cleaning – Provide good ventilation and warmth for normal drying. Two coats will provide best durability and uniformity. Clean up with mineral spirits.

SHIPPING

Freight Classification:	Packaging:	Flash Point:
Paint, Combustible Liquid	1 gallon (3.785L) 1 quart (0.946 L)	40°C (101°F)

⚠ LIMITATIONS OF LIABILITY

The information in this data sheet is based on laboratory tests we believe to be accurate and is intended for guidance purposes only. All recommendations or suggestions relating to the use of the products made by Caribbean Paint Factory Aruba, whether in technical documentation, or in response to a specific inquiry, or otherwise, are based on data which to the best of our knowledge are reliable. The products and information are designed for users having the requisite knowledge and industrial skills and it is the end user's responsibility to determine the suitability of the product for its intended use. Caribbean Paint Factory Aruba has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Caribbean Paint Factory does therefore not accept liability arising from loss, injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise) The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is therefore the user's responsibility to ensure that this sheet is current prior to using the product. The English text of this document shall prevail over any translation thereof.

8050- X– November 2009



Caribbean Paint Factory Aruba Inc.
Tel: +297 - 5825339
Fax: +297 - 5837063
Sabana Blanco 16A
Oranjestad - Aruba

