



Caribbean
Paint
Factory
Aruba Inc.

EUROLIFE®

Interior/Exterior Semi-Gloss Transparent Stain
DS 8120X

DESCRIPTION

A premium wood preserving transparent stain based on an alkyd resin for interior & exterior decoration. Protects and embellishes wood grain and texture. Produces beautiful stain colors that enhance wood tones. Recommended for above ground use on all types of wood with a porous surface. Not recommend for sealed or non porous surfaces.

FEATURES

- ▶ Penetrating protection, will not peel, blister or crack
- ▶ Good color retention
- ▶ Highlights wood's natural grain and texture
- ▶ Water repellent
- ▶ Good weather and UV resistance

- ▶ Mildew resistente

COMPOSITION

- ▶ Alkyd Resin
- ▶ Water repellents

SPECIFICATION DATA

Color:
Clear & Custom Colors

Finish:
Semi-Gloss

Clean up solvent:
Mineral Spirits

Density:
7.83 lbs/gal (0.94 kg/L)

VOC:
2.04 lbs/gal (245 g/L)

Solids:
Volume: 44% +/- 2%

Practical coverage:
Apply at 350-450 sq ft/gal (9-11 m²/L)
Actual coverage depending on type and structure of substrate and application method

Dry Time:
77°F (25°C) & 50% RH:
To touch – 2 hours
To recoat – Overnight



FINISHES
PAINTING (08900)

! Read Label and Material Safety Data Sheet Prior to Use.
See other cautions on last page.

www.cpfaruba.com

Caribbean Paint Factory Aruba Inc.
Tel: +297 - 5825339
Fax: +297 - 5837063
Sabana Blanco 16A
Oranjestad - Aruba

SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, loose and flaking paint and other foreign substances.

NEW WOOD SURFACES: Remove grade stamps or pencil marks by light sanding. Stain with this product. Wood with mill glaze (slick, shiny appearance) must be scuff sanded or weathered and pressure washed before staining. Pressure-treated wood must be dry before applying stain. All new wood (treated or untreated) should be stained as soon as possible.

WEATHERED BARE WOOD: Remove mildew by washing with a solution of 16 oz (473 mL) liquid household bleach and two oz (59 mL) non-ammoniated liquid detergent per gallon (3.785 L) of water. Rinse well and let dry 24 hours before staining.

DIRECTIONS FOR USE

Tools – May be applied by brush, roller or spray. On horizontal siding, stain several boards all the way across to a natural break. AVOID HEAVY APPLICATIONS OR PUDDLING ON SURFACES. REMOVE EXCESS BEFORE DRYING. For airless spray use a 0.13" tip. Adjust pressure as needed. Do not apply in damp weather or when surface or air temperature is below 4°C (40°F)

Painting & Cleaning – Provide good ventilation and warmth for normal drying. Two coats will provide best durability and uniformity. Clean up with mineral spirits.

SHIPPING

Freight Classification:

Paint, Combustible Liquid

Packaging:

1 gallon (3.785L)

1 quart (0.946 L)

Flash Point:

45°C (114°F)

! LIMITATIONS OF LIABILITY

The information in this data sheet is based on laboratory tests we believe to be accurate and is intended for guidance purposes only. All recommendations or suggestions relating to the use of the products made by Caribbean Paint Factory Aruba, whether in technical documentation, or in response to a specific inquiry, or otherwise, are based on data which to the best of our knowledge are reliable. The products and information are designed for users having the requisite knowledge and industrial skills and it is the end user's responsibility to determine the suitability of the product for its intended use. Caribbean Paint Factory Aruba has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Caribbean Paint Factory does therefore not accept liability arising from loss, injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise) The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is therefore the user's responsibility to ensure that this sheet is current prior to using the product. The English text of this document shall prevail over any translation thereof.

DS 8120X – November 2009

www.cpfaruba.com

Caribbean Paint Factory Aruba Inc.
Tel: +297 - 5825339
Fax: +297 - 5837063
Sabana Blanco 16A
Oranjestad - Aruba

