



**Caribbean  
Paint  
Factory  
Aruba Inc.**

## EURO LIME PLASTER®

Interior Natural Lime Plaster  
8400-X

### DESCRIPTION

A one of kind interior lime plaster finish for use on properly prepared drywall, masonry, brick and tilt-concrete surfaces. Provides a hard flat or shiny finish, incorporating a color depth that can only be created using this type of material. Used for residential and commercial applications.

### FEATURES

- ▶ High permeability, no moisture entrapment
- ▶ Energy efficient, offers natural thermal comfort.
- ▶ A natural biocide, mold & mildew resistant
- ▶ Good level of elasticity, adjusts to structure movement.
- ▶ Waterproof by nature
- ▶ Non – combustible
- ▶ Easy to maintain and clean
- ▶ Exceptional durability
- ▶ No color fading through UV exposure
- ▶ Zero VOC base and pigments.

### COMPOSITION

- ▶ Natural lime and fine powder aggregates
- ▶ Earth Pigments
- ▶ Not manufactured with any chemical material

### SPECIFICATION DATA

Clean up solvent:

Water

Density:

N/A

VOC:

None

Solids:

N/A

Practical coverage:

Apply at 50 – 100 sq ft/gal

Actual coverage depending on type and structure of substrate and the number of passes

Dry Time:

77°F (25°C) & 50% RH:

To touch – ½ to 1 hour

To float – 2 – 3 hours

ⓘ Read Label and Material Safety Data Sheet Prior to Use.  
See other cautions on last page.

[www.cpfaruba.com](http://www.cpfaruba.com)

Caribbean Paint Factory Aruba Inc.

Tel: +297 - 5825339

Fax: +297 - 5837063

Sabana Blanco 16A

Oranjestad - Aruba

## SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, rust scale, loose and flaking paint and other foreign substances.

### NEW SURFACES

**Concrete, Plaster and Masonry** – Poured concrete or pre-cast concrete needs appropriate high pressure cleaning and removal of residue. Rinse completely with water and allow to dry. Remove loose aggregate and prime with acrylic primer or surface leveling primer. For concrete block, fill and level with Silica Tec Plastec.

### PREVIOUSLY PAINTED SURFACES

Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose or peeling paint to sound surface by high pressure water cleaning. Remove all mildew by washing with a solution of 16 oz (473 mL) liquid household bleach and two oz (59 mL) non-ammoniated liquid detergent per gallon (3.785 L) of water. Rinse surface clean with water and allow to dry. Prime with any suitable acrylic based primer.

## DIRECTIONS FOR USE

Tools – Commonly applied with stainless steel throwel.

Installation & Cleaning – 1st coat is floated [0.5 mm] with a steel throwel as a normal plaster. 2nd coat will be applied very thin as a skim and floated again with a steel throwel. In other to facilitate polishing a diluted black soap is sprayed on the surface or the throwel and floated again, this time firmly pressed. Polishing with natural wax is normally done 2 to 3 days after installation.

## SHIPPING

Freight Classification:	Packaging:	Flash Point:
Non - Combustible	4 gallon (15.14 L) 0.8 gallon (3.02 L)	None

## ! LIMITATIONS OF LIABILITY

The information in this data sheet is based on laboratory tests we believe to be accurate and is intended for guidance purposes only. All recommendations or suggestions relating to the use of the products made by Caribbean Paint Factory Aruba, whether in technical documentation, or in response to a specific inquiry, or otherwise, are based on data which to the best of our knowledge are reliable. The products and information are designed for users having the requisite knowledge and industrial skills and it is the end user's responsibility to determine the suitability of the product for its intended use. Caribbean Paint Factory Aruba has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Caribbean Paint Factory does therefore not accept liability arising from loss, injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise) The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is therefore the user's responsibility to ensure that this sheet is current prior to using the product. The English text of this document shall prevail over any translation thereof.

8400-X – November 2009

[www.cpfaruba.com](http://www.cpfaruba.com)

Caribbean Paint Factory Aruba Inc.  
Tel: +297 - 5825339  
Fax: +297 - 5837063  
Sabana Blanco 16A  
Oranjestad - Aruba

